

# AJ-2008TX (EPSON I3200-A1x8)

2m High Speed Dye Sublimation Printer

**NEW  
UPDATE!**



Sublimation Ink

C M Y K / C M Y K Lc Lm Lk LLk

Fy Fm Re Or Gr Bl Spot Colors Optional

Authorization Licensing  
Powered by **ORIC**

Eight I3200 Heads  
CMYK



Both the sublimation and direct-to-textile printers are examples of our expertise and engineering: top performant, reliable and precise. With Ainkjet series printer, you can maximize production while controlling quality and minimizing costs for beautiful soft signage, apparel and interior decor items that will set your business apart from the competition.

Wide applications in clothing, home decoration fabrics, sampling, shirt, canvas bags, bolster, scooter, flags, textile gadgets etc.




\* 2.0m 8\*I3200-A1 Print Heads Speed (4 Colors)

360x1200dpi - 1pass

380 m<sup>2</sup>/h

360x2400dpi - 2pass

180 m<sup>2</sup>/h



(3000m Jumbo media load)

## ● Technical Specifications


<b>Model</b>	AJ-2008TX	
<b>Print Head</b>	Eight I3200 Print Heads	
<b>Droplet Size</b>	3.5pl	
<b>Printing Technology</b>	Piezoelectric Inkjet	
<b>Acceptable Media</b>	Width	2000(mm)
	Thickness	≥30g
	Outer Diameter	210 mm(8.3in)
	Bearing Meter	3000m
<b>Ink Cartridges</b>	Type	220ml secondary ink tank + 5L ink bottle
	Color	CMYK/CMYK+LCLMLKLLK/FM、FY、RE、GR、OR、BL
	Supply	Siphon ink path system + automatic refill ink system
<b>Print Media</b>	Heat Transfer Paper	
<b>Printing Resolution</b>	Maximum 1200 dpi	
<b>Printing Speed</b>	1pass(720x600dpi): 4090sqft (380sqm/h)	
	2pass(720x600dpi): 2421sqft (225 sqm/h)	
<b>Media Loading and Take-up</b>	Automatic Air Expansion Shaft System	
<b>Dryer</b>	External Automatic Air/ Heat Integrated Dryer	
<b>Moisturizing</b>	Automatic Cleaning and Moisturizing Integrated Unit	
<b>RIP Software</b>	Maintop6.0、Photoprint、Onyx、NeoStampa、PrintFactory (Ultraprnt as standard and other softwares optional)	
<b>File Format Supported</b>	JPG / TIFF / PDF, etc	
<b>Interface</b>	USB 3.0	
<b>Power</b>	printing system : 2000W    Drying system : Maximum 8000W	
<b>Power Supply</b>	AC 220V ± 5%, 16A, 50HZ±1	
<b>Dimensions(with stand)</b>	139.7(W)x62.6(D)x77.5(H) in.	
	3550(W)x1590(D)x1970(H) mm	
<b>Weight(with stand)</b>	2645 lb. (1200 kg)	
<b>Environment</b>	Temperature: 59 ℉ to 90 ℉ [15℃ to 32℃] (68 ℉ [20℃] / Humidity: 35 to 80% (No Condensation)	
	Temperature: 41 ℉ to 104 ℉ [5℃ to 40℃] / Humidity: 20 to 80% (No Condensation)	
<b>Accessories</b>	External Automatic Control Air And Heat Integrated Dryer, Low-ink Alarm System, Double air-shaft Media Loading And ta-up System, Automatic Moisturizing Cleaning System	




Wider and thicker girder with THK silent double guide rails




Mirror baffle, easy to observe the nozzle condition and maintenance




Feeding adopt servo motor, make the paper more stable and more accurate




Pressure wheel material upgrade pressure wheel density increase, make paper feed more uniform stability




Vertical groove guide gas platform, make paper surface more smooth



Swing rod upgrade optimization for increased strength and stability



Motor uses AC servo motor to make the trolley movement smoother and the printing point more accurate



Inflatable shaft upgrade is sliding type, convenient materials up and down