

CEFIRA LAMINATION FILM 120Gr

PRODUCT DESCRIPTION:

Cold Lamination Film, 120gr, matte or glossy, PVC film with acrylic pressure sensitive adhesive.

PRODUCT SPECIFICATIONS:

Composition	monomeric calendered PVC.
Thickness Vinyl	80 micron.
Surface	Matte/Glossy.

SOLVENT ACRYLIC PRESSURE SENSITVE GELATIN:

Glue	Permanent.
Glue thickness	16-18 micron.
Glue weight	30-35gsm.
180° Peel off strenth	≥ 8-10N.

LINER:

J	100 gsm raw premium paper with green lines.
Ī	One side 20(+/-5)gsm PE treated and siliconized.
ĺ	Release strength: 20g, ≥ 3-5 seconds.

SIZE: 1,07 / 1,37 / 1,52m X 50M.

PACKING: 1roll/carton.

SHRINKAGE: shrink in 3 indoor for one year.

SHELF LIFE: 12 months.

TEMPERATURE RESISTANCE:

Betweeng -30 and +70 °C

OUTDOOR EXPOSURE:

Accelerated weathering tests indicate that Cefira Laminado 120gsm have an expected outdoor life of 1 years. Accelerated weathering tests simulate exposure in a middle European climate. It is essential to note that many arbitrary factors will affect the outdoor durability of all inks, ink deposit, media, climate and position etc.

STORAGE:

Recommend storage between temperature 10-30 degree centigrade, and 35 - 65% relative humidity. Keep all finished rolls on horizontal position, avoid from direct sun light.

Our Products are intended for sale to professional users. The information herein is general information designed to assist customers in determining the suitability of our products for their applications. All recommendations are made without guarantee, since the application and conditions of use are beyond our control. We recommend that customers satisfy themselves that each product meets their requirements in all respects before commencing a print run. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In no event shall Brigal be liable for damages of any nature arising out of the use or reliance upon this information. Modifications of the product for reasons of improvements might be made without further notice.