

TECHNICAL DATA SHEET



S-RACE® Tacky 100

Product line: S-RACE® Select

Grade: J30100

Microporous Coated Thermal Adhesive Dye Sublimation Paper

Product specification*

Grammage: 100 g/m² ± 6 g/m²
Thickness: 127 µm ± 6 µm
5.0 mil ± 0.25 mil

Benefits

- › Optimal tack between paper and fabric during sublimation transfer (no ghosting)
- › Extremely fast drying
- › Excellent line sharpness
- › Superb and quick transfer properties
- › Outstanding lay-flat performance
- › Exceptional quality consistency

This product is fully recyclable.

Key applications

- › Transfer on all kinds of polyester textiles
- › Especially designed for elastic textiles. No movement between paper and fabric during transfer (eliminates possible ghosting effect)
- › For medium to high ink coverage

Width (cm)	Roll diameter (mm)	Core (inch)
61.0	120 – – – – – – –	3
111.8	– 150 170 250 300 400 500 1000	3
162.0	– 150 170 250 300 400 500 1000	3

Other specifications on request.

Please note: the outer side of the roll is the printing side.

Storage

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

*Modifications reserved.